

CM
SAFE CO

PREMIER HIGH SECURITY SAFES



for the security conscious



CMI SAFE CO

Head Office: 244 WEST STREET, CARLTON, N.S.W. 2218

Phone: (02) 9547 1488 (5 LINES) Fax: (02) 9547 2104

Web site: <http://www.cmisafe.com.au> Email: sales@cmisafe.com.au

ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT & TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.

CMI PREMIER RANGE (T.D.R.)

Heavy duty safes of Australian design and manufacture, utilising some of the most modern techniques and materials recently developed in security technology.

The design features and defensive materials used result in a safe giving a high level of resistance to cutting instruments, explosives and force, and pneumatic and hydraulic tools.

Both the body and door of the safe are resistant to attack with Oxy-acetylene.

CMI safe Co. has been designing, manufacturing and servicing safes throughout Australia for more than 50 years. CMI safes are used by all State and Federal governments and many of Australia's leading national companies, banks and building societies.

DOOR: The door of the Premier safe has an overall thickness of 135mm, and the 55mm thick defensive slab section contains metals highly resistant to drills and abrasive grinders in addition to the high-strength poured barrier materials and other defences.

The lockcase forms and integral part of the entire door structure, giving additional strength.

BODY: The body gives a minimum thickness of 75mm of high-density refractory materials at all points. These materials are bonded between inner and outer walls of specially reinforced steel, becoming a complete monolith after pouring. The engagement of the door and body effectively result in a continuous cube of exceptional strength and security.

INSURANCE COVER:

A conservative suggested risk rating for premier range safes overnight holding of cash and valuables would be \$45,000.00 in an unsupported situation.



PREMIER MODEL PR3 IS SHOWN ON THIS LEAFLET

LOCKING: One million variations are available on the three wheel high quality combination lock.

Changes to the combination are easily made by "Premier" Safe owners. A special glass-activated relocking device and mechanical relockers are provided within the door. A six lever keylock if fitted as standard equipment. Each lock can be used independently from the other.

BOLTWORK: Heavy 25mm dia. bolts of high grade steel provide two-way locking into the specially strengthened lock chamber sections at front and rear edges of the door.

BOLT-DOWN FACILITY: Two recessed bolt-down holes are provided in the base of the safe to allow secure anchoring to any type of floor.

FINISH: CMI "Premier" safes are available in attractive hammertone durable finishes to suit any office decor. Satin finish handles, locks and fascia panels complement the high quality appearance.

INTERNAL FITTINGS: All models except PRB have two lockable drawers and two adjustable shelves.

FIRE RESISTANCE

The premier safe has been designed to give one hour fire resistance.

Model	Code	Height	Width	Depth	Weight Kg	Litres	Locking Points	Price
PRB	External	615 mm (24")	460 mm (18")	510 mm (20")	308	39	4	\$
	Internal	460 mm (18")	300 mm (12")	280 mm (11")				
PR1	External	660 mm (26")	560 mm (22")	560 mm (22")	372	68	6	\$
	Internal	508 mm (20")	405 mm (16")	330 mm (13")				
PR2	External	770 mm (30")	615 mm (24")	660 mm (26")	500	122	6	\$
	Internal	615 mm (24")	457 mm (18")	435 mm (17")				
PR3	External	920 mm (36")	615 mm (24")	660 mm (26")	568	152	6	\$
	Internal	762 mm (30")	457 mm (18")	435 mm (17")				
PR4	External	1075 mm (42")	660 mm (26")	660 mm (26")	704	202	8	\$
	Internal	910 mm (36")	510 mm (20")	435 mm (17")				
PR5	External	1075 mm (42")	765 mm (30")	850 mm (33½")	926	327	8	\$
	Internal	910 mm (36")	610 mm (24")	585 mm (23")				
PR6	External	1225 mm (48")	765 mm (30")	850 mm (33½")	1026	381	8	\$
	Internal	1066 mm (42")	610 mm (24")	585 mm (23")				
PR7	External	1375 mm (54")	765 mm (30")	850 mm (33½")	1128	435	10	\$
	Internal	1220 mm (48")	610 mm (24")	585 mm (23")				
PR8	External	1525 mm (60")	765 mm (30")	850 mm (33½")	1230	489	10	\$
	Internal	1370 mm (54")	610 mm (24")	585 mm (23")				
PR9	External	1675 mm (66")	765 mm (30")	850 mm (33½")	1345	542	10	\$
	Internal	1520 mm (60")	610 mm (24")	585 mm (23")				
PR10	External	1825 mm (72")	765 mm (30")	850 mm (33½")	1464	595	10	\$
	Internal	1675 mm (66")	610 mm (24")	585 mm (23")				

(Important: Please allow 55mm projection for door furniture on depth measurement)

CD PONT 017 KB 1999

CMI Safe Co. reserve the right to alter specifications without notice or obligation.

To deliver and install level access metro \$

Agents in all major cities throughout Australia.



MADE IN AUSTRALIA